

Uporaba tekmovalnih pnevmatik KUMHO

Profil	Uporaba	Sp. Ch.	Zmes	Priporočena uporaba		
				Vroč tlak (Bar)	Temp. vozišča (°C)	Temp. tekalne površine (°C)
R700	Rough Gravel Rally	3B	K90	2.2 ~ 2.8	30 ~ 50	60 ~ 90
		3C	K70	2.2 ~ 2.8	10 ~ 40	60 ~ 90
R800	Mild Gravel Rally	3B	K90	2.2 ~ 2.8	35 ~ 50	60 ~ 90
		3C	K70	2.2 ~ 2.8	25 ~ 45	60 ~ 90
		3D	K31	2.2 ~ 2.8	10 ~ 35	50 ~ 90
C03	Tarmac Rally	3A	K90	1.9 ~ 2.5	30 ~ 50	60 ~ 110
		3B	K60	1.9 ~ 2.5	25 ~ 45	60 ~ 110
		3E	K50	1.9 ~ 2.5	20 ~ 40	60 ~ 110
		3C	K21	1.9 ~ 2.5	15 ~ 35	50 ~ 100
		3D	K11	1.9 ~ 2.5	10 ~ 30	50 ~ 100
TW01	Tarmac Wet	3C	K21	1.8 ~ 2.4	15 ~ 45	50 ~ 80
		3D	K11	1.8 ~ 2.4	5 ~ 35	50 ~ 80
TW02	Tarmac Wet Siped	3C	K21	1.8 ~ 2.4	15 ~ 45	50 ~ 80
		3D	K11	1.8 ~ 2.4	5 ~ 35	50 ~ 80
V70A	On Road Circuit	3B	K90	2.0 ~ 2.5	30 ~ 50	80 ~ 120
		3C	K60	2.0 ~ 2.5	20 ~ 45	80 ~ 120
	Tarmac Rally	3D	K21	2.0 ~ 2.5	10 ~ 25	60 ~ 110
V700	On Road Circuit	3C	K80	2.0 ~ 2.5	10 ~ 45	80 ~ 120
V710	On Road Circuit	3C	K60	2.0 ~ 2.5	10 ~ 45	80 ~ 120
S700	GT & Touring Slick	3G	K60	1.8 ~ 2.2	25 ~ 50	80 ~ 120
		3D	K40	1.8 ~ 2.2	20 ~ 45	80 ~ 120
		3B	K50	1.8 ~ 2.2	15 ~ 40	80 ~ 120
	Formula Slick	3A	K6G	1.5 ~ 1.8	10 ~ 45	80 ~ 120
		3B	K50	1.5 ~ 1.8	10 ~ 45	80 ~ 120
		3C	K45	1.5 ~ 1.8	10 ~ 45	80 ~ 120
		3D	K6G	1.5 ~ 1.8	10 ~ 45	80 ~ 120
W700	GT & Formula Wet	3C	K21	1.4 ~ 2.0	5 ~ 25	40 ~ 60